SEVERE DUTY — OILFIELD TYPE TRAILERS

We offer custom oilfield trailers designed & built for specific purposes. Standard lengths are through 53' with longer lengths available upon request.

Standard Models available are:

- Flat Bed (Float)
- Single Drop Deck
- Double Drop Deck (Low Boy)
- Extendable (Stretch) Option available for all drop & flat models
- Coil Tubing Trailers
- Other designs can be considered based on design review

Frame Structures vary with model design

Popular frame options include:

- 6" Structured side rail standard
- Inverted 5th Wheel Under Gooseneck
- Multiple King Pin Settings on Same Trailer
- Flip Neck
- Draw Bar on Front of Gooseneck Narrow Neck Gooseneck with
- Roller in Rear Center
- Removable Gooseneck with Tapered approach on nose of bottom deck
- Full width roller on rear of gooseneck
- Frame width roller rear of gooseneck with heavy wall 1/2 pipes on outsides
- Heavy Wall 1/2 pipe across top rear edge of gooseneck
- Pop-Up Rollers in Bottom Deck
- 4 Beam Frames
- 8-5/8" Tail Roller with Apron
- 10-3/4" Tail Roller with Apron
- Folding Landing Legs

Systems Standard option 25,000# Axles with 25,000# Suspensions

Axle & Suspension

Popular Options Include:

- Multiple Axles Available
- Axle Lift Kit • 30.000# Axles
- 30,000# HT300 Suspension
- 2 Axle Heavy-Duty Single Point Spring Suspension Walking Beam Spring Suspension

Tires & Wheels

- Continental Tires Standard in 17.5 size
- 22.5" & 24.5" Low & Tall Profile
- Michelin Tires Optional in sizes of 17.5", 22.5" & 24.5" Low & Tall Profile
- Other brands & sizes are available upon request
- Steel wheels are standard on all models
- Polished Alum. Wheels optional
- Milled Alum. Wheels optional
- Accu-Shield Wheels optional
- Spare Tires, Wheels & Tire Carriers optional

Air & Electrical

4S/2M ABS system standard on all models with air to meet FMVSS

- Popular Options Include:
- Manual Suspension Dump Valve Auto Dump when Set Park Brakes
- Electric Dump Kit with Auto-Lockout installed on rear axle
- Air Raise & Lower Valve in either Plastic or Aluminum box
- P.S.I. Air Inflator System Axles
- Crossfire's
- Pull Lanyards on Air Tanks
- Air Weigh or Right Weigh Air Scale Systems
- Liquid Filled Air Gauge

Grote wiring harness and lights are standard per model design to meet FMVSS

Popular Options Include:

- Extra lights available per custom specifications
- Strobe Lights
- Backup Lights
- Over Dimension Lights
- Dual A&E—Glad Hands & 7-Way in 2 Locations
- Aux. 4-Way Plug in Front Bumper with Harness
- 4-Way Plug in any other location
- Aux. 7-Way Plug in Front Bumper with Harness
- 7-Way Plug on rear

Flooring

1-1/8" Apitong is standard on 1/2" & less top flanges • General Tires Standard in sizes of 1-3/8" Apitong is standard on 5/8" & greater top flanges Popular Options Include:

- 1/4" Steel plate over Suspension area, Apitong wood forward
- 3/8" Steel plate over Suspension Area, Apitong wood forward
- Steel plate in bottom of gooseneck • Steel plate on top of Narrow Neck gooseneck
- Steel in lieu of wood floor

Popular Load Securement **O**ptions

- Aluminum Winch Track
- Winch Strap Rail under Cross Members
- Sliding Winch
- Weld-On Winch
- 3-Bar Winch
- 5/8" D-Rings
 - 9/16" D-Rings • 1" D-Rings
 - Recessed Chain Ties
 - 1-9/16" Pin Pockets parallel with front axle & tail roller
 - side rail • Round Pipe Pockets 4" I.D. x 15"


• 1-9/16" Pin Pockets welded along

- with gussets
- 3.5" O.D. x 50" Round Stakes
- Folding racks for pipe stakes • L Type Chain Anchor for 4 beam trailer only

Popular Accessories & Misc.

- Chains on axles
- Axle Straps
- Timber Rack under bottom deck
- Tool Boxes, Aluminum or Steel Belly Box











Pipe Pockets Pipe Stake Carriers



Designers and builders of specialized trailers since 1974

800-734-0608 www.doonan.com

Not all options are compatible with other option combinations. Custom options are available upon request. Doonan Specialized Trailer, LLC reserves the right to make changes in material, components, design, equipment specifications and trailer models without notice. All visual specifications, representations, and dimension references are based on the latest product offering and are approximations available at the time of publication. At no time will the information contained within this publication be used as a basis for resolving disputes.







36 NE Highway 156 • Great Bend, Kansas 67530 • Telephone (620) 792-6222 • Fax (620) 792-3308

